

Venue & tech specifications 2017

Parkteatret Scene, Olaf Ryes Plass 11, 0552 Grünerløkka, Oslo, Norway www.parkteatret.no

CONTACT: info@parkteatret.no Switchboard: + 47 22356300. Fax: + 47 22356297
Daily manager/booking: Limita Lunde limita@parkteatret.no + 47 90019041
Production manager: Kjell André Nilsen kjella@parkteatret.no + 47 93209082
Technical manager: Hilmar Bergendahl Larsen hilmar@parkteatret.no + 47 92608636
Parkteatret Bar: Dan Michael Danino dan@parkteatret.no + 47 93288002

CAPACITY: 500 standing.
Depending on set-up: 130 seated/330 mixed (On the small stage:120 standing)

LOAD IN: Street level into hall. No ramp accessible.

POWER: DELTA-system 230V/50Hz (blue); 3 phases + ground, - but no neutral. 230V between the three phases. 130V between phases and earth. Main output for stage is provided with 200A total.
3-phase: 3 x 63A (363-9, CEE-form), 9 x 32A (332-9, CEE-form: used for house dimmers), 80A "flat".
2-phase/Single phase: 12 x 16A (216-6, schuko F-type) 6 of these are free to use.
Outside venue: 1 x 16A (schuko F-Type)

MEASUREMENTS:

The main stage: 8m x 5,25m (This is the active inner size; for performance.)
The first meter downstage consists of Prolite stage decks. Height from floor: +/- 1,12m.
From stagefloor to roof: 4,15m – 5m. Tiny side stages.
Hall: 14,5m wide x approx. 19m deep. Lowest part of hall is angled approx. 6 degrees and has 6,4m height. Upper part of the hall is with level floor and 3,5m height, - floor to ceiling.
The small stage: (located back in the upper part of the hall) Size: 3,25m wide x 3,9m depth. Height from floor 15 cm.

SOUND EQUIPMENT: (No monitormix at Parkteatret)

Main PA: Speakers are in fixed positions and system have locked system processors.
Speakers: 6 x L'Acoustics ARCslI / 6 x L'Acoustics SB18i. Subs are center mono cardioid configured.
Amplification: 3 x L'Acoustics LA8 and 1 x L'Acoustics LA4.
Frontfill: 4 x L'Acoustics 8XTi

F.O.H: (on wheels)
Yamaha CL5 (Same mixer for the main stage & the small stage)

Ins/Outs: (at Stage Right)
Rio3224-D, Ri8-D and Rio1608-D Yamaha Stage racks. (56 inputs/32 outputs)

Monitor system: (8 programs)
10 x Turbosound TMW 115, Bi-amped.
1 x Meyer HP600 powered sub.
2 x Lab C68:4
2 x Lab C48:4.

Stagemultis: 3 x Stagemulti 12 send, 3 x Stagemulti 4 send. (Ends at Stage Right)

Small stage PA: PA: 2 X EAW NT-29 (self powered tops) +
1 x Meyer HP600 powered Sub.
16 inputs in mobile Rio stagerack. Monitors: 3 programs from mainstage.

Microphones:

9 x Shure Sm58
2 x Shure Beta58A
3 x Shure Beta57
6 x Shure Sm57
1 x Neumann KMS105
1 x AKG D5
2 x Sennheiser e606
1 x Shure Beta52
1 x Shure Beta91A
3 x Sennheiser e604
1 x Sennheiser e904
1 x Sennheiser MD 421
4 x Neumann KM184
3 x Røde NT-5
2 x Neumann TLM103

DI's: 8 x BSS AR-133, 2 x Klark DN100, 1 x Klark DN200 (stereo).

Stands K&M: 12 low with boom, 15 tall with boom.

Wireless frequencies: The available legal bands for wireless equipment in our area:

510 - 526 MHz (K26-27)

534 - 542 MHz (K29)

550 - 558 MHz (K31)

566 - 574 MHz (K33)

582 - 606 MHz (K35-37)

614 - 622 MHz (K39)

678 - 686 MHz (K47)

694 - 710 MHz (K49-50)

726 - 742 MHz (K53-54)

750 - 758 MHz (K56)

774 - 782 MHz (K59)

dB-limits:

Parkteatret is enforcing a dB limit of 102 dBA average over 15 minutes (Leq 15=102 dB(A)). Values will be measured at FOH. Parkteatret doesn't use a peak limiter or circuit breaker to enforce the rule, but our Production Manager (PA) will engage in reducing the overall sound level if rules are not complied with. Shows for under-18 should be kept at a lower level than.

LIGHT EQUIPMENT: Houselighting is fixed and permanently rigged!

Mixer: grandMA2 ultra-light

Dimmers: Zero88 Betarack 54 x 10 Ampere (9 channel racks x 6 dimmerchannels á 10 Ampere).

Permanent mounted fixtures:

6 x Clay Paky B-Eye K10 (Fixed mounted in the permanent back truss)
2 x Atomic 3000 strobes (Fixed mounted in the permanent back truss)
24 x par 64 1000W in trusses
8 x scrollers for Par 64
6 x High End SolaSpot Pro 1000 (Fixed mounted, in the motorized back truss)

4 x 2-lights (Fixed mounted, in the motorized back truss)
4 x Selecon Rama 1200W fresnels (frontlight)
3 x ETC SourceFour Zoomprofiles 750W (15-30 degrees).

Loose fixtures:

2 x Twolights
6 x 1000W floorcans
4 x Martin Rush Strobe CWL - LED

6 channels extension cables from stage to dimmers.

Hazer: HazeBase - base*hazer*pro

Mirrorballs: 2 x 40cm with motors in hall truss.

Stage-decks/risers: 6 x 2m x 1m. Prolyte, standard. 40 cm legs.

Mountings:

A. Upstage/Back of stage: A permanent truss, laying from the each side of the outer walls. (ø48.3mm Litec QD40 truss, 0.40m x 0.40m) Used for backlighting, backdrops etc. Outer width: 12.5m. Height from stagefloor: Approx. 4,2m. Maximum point load: 360kg. Max total load, evenly distributed over the truss: 1100kg.

B. Upstage (in front of B): 8m truss on two hoists for external heads etc. (Prolyte H30V, ø30mmx30mm) Maximum point load per meter: 125kg. Max total load, evenly distributed over the truss: 1000kg.

C. Downstage/proscenium: A permanent standing truss (ø48.3mm Litec QD40 truss, 0.40m x 0.40m). Outer width: 13m. Outer height: approx. 6m. Maximum point load: 360kg. Max total load, evenly distributed over the truss: 900kg. (The PA-speakers are hung permanently in this truss.)

D. Hall: Rectangle truss - 13m x 13m x 3m x 3m. (Prolyte H30V, ø30mmx30mm) Prolyte truss on four hoists. Maximum point load per meter: 125kg. Max total load, evenly distributed over the truss: 2000kg.

Screens for projection:

1: Screen on the stage: 6m x 4,3m. Motorized rollsystem over the stage, permanent installed.
2: Cyclorama: 8m x 4,5m. Hanging behind rear curtain.

Curtains, black: Act/main curtain: 8m x 4,5m. 2-part symmetrical system on rails, manually drawn.
Back curtain: 11m x 4,5m. 2-part symmetrical system on rails.
Legs/Side curtains: 4,25m x 4,5m. 2-part system on rails on both sides.

BACKLINE RENTAL / Not included in the rental:

Ampeg SVT Classic, SVT15E, SVT410HE: **800,-** NOK

Fender '65 Twin Reverb: **600,-** NOK

Vox AC30 CC2: **600,-** NOK

Drumkit: **1000,-** NOK (no snaredrum, no cymbals or hi hat cymbals)
Gretch Renown Maple. Dimensions: 22` x 18` bassdrum, 10`, 12`, 14`, and 16` toms. Finish: Silver Slate Sparkle.

Hardware: Bassdrum pedal (Gibraltar), clamp for rack tom, stand for snaredrum (Pearl), stand for hi hat (Gibraltar), 2 cymbalstands with boom (Yamaha, DW) 2 straight cymbal stands (Gibraltar, DW).

Clavia, Nordstage 88EX / stand / sustain pedal: **800,-** NOK

(No DJ rig at Parkteatret.)

Grand Piano: Bohemia, 225 Smetana, black. **3000,-** NOK Tuning **3000,-** NOK

Projector: We offer rental of a projector, cables and mounting system. Contact us for further information. Screens are mounted on stage.